

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
16 October 2003 (16.10.2003)

PCT

(10) International Publication Number  
WO 03/085449 A1

(51) International Patent Classification: G02F 1/1335

(21) International Application Number: PCT/TB03/01462

(22) International Filing Date: 10 April 2003 (10.04.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
2002-108978 11 April 2002 (11.04.2002) JP

(71) Applicant (for all designated States except US): KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventor; and

(75) Inventor/Applicant (for US only): HAMAWAKI, Yoshihiko [JP/JP]; c/o Philips Japan, Ltd., Philips Bldg., 2-13-37, Kohnan, Minato-ku, Tokyo 108-8507 (JP).

(74) Agent: AOKI, Hiroyoshi; c/o Philips Japan, Ltd., Philips Bldg., 2-13-37, Kohnan, Minato-ku, Tokyo 108-8507 (JP).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report  
— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: TRANSFLECTIVE LIQUID CRYSTAL DISPLAY DEVICE AND METHOD OF MANUFACTURING THE SAME.



(57) Abstract: To provide a transflective liquid crystal display device in which an amount of reflected light can be increased in a reflective mode. A liquid crystal panel (10) has a first glass substrate (101) and a second glass substrate (105). A backlight (11) is placed on the outside of the liquid crystal panel (10). A transmissive region (102) has a rectangular shape and is arranged in the center of the pixel. A reflective region (103) is arranged around the transmissive region (102). A reflecting layer (104) is formed in the reflective region (103) of the first glass substrate (101). A scattering layer (106) is formed in the transmissive region (102) of the second glass substrate (105).

TRANSFLECTIVE LIQUID CRYSTAL DISPLAY DEVICE AND METHOD OF  
MANUFACTURING THE SAME.

BACKGROUND OF THE INVENTION

5 1. Field of the Invention

The present invention relates to a transflective liquid crystal display device and a method of manufacturing the same. More particularly, the present invention relates to a transflective liquid crystal display device in which an amount of the reflected light can be increased in the reflective mode.

10

2. Description of Related Art

So-called transflective liquid crystal display devices have been put into full-scale practical use in which outside light incident from a front side is reflected to lead to the front side, while incident light from a rear side due to the backlight system is transmitted to lead to  
15 the same front side. The liquid crystal display devices of this type provide effective image display by the outside light (ambient light) principally (reflective mode) under well-lighted environments, and by the emitted light in the backlight system principally (transmissive mode) under low-lighted environments.

Such a type of liquid crystal display device is disclosed in a document of the related  
20 art of M.Kubo, et al. "Development of Advanced TFT with Good Legibility under Any Intensity of Ambient Light", IDW'99, Proceedings of The Sixth International Display Workshops, AMD3-4, pages 183-186, Dec. 1, 1999, sponsored by ITE and SID".

In this device, each pixel has a reflective region and a transmissive region. The reflective region is provided with, for example, an aluminum reflecting member. Removing  
25 the reflecting member partially forms the transmissive region. For example, the transmissive region is disposed at the center in a rectangular pixel region and has a rectangular shape substantially geometrically similar to the pixel region. The reflective region is a portion of the pixel region except the rectangular transmissive region and has a shape of surrounding the transmissive region.

30

SUMMARY OF THE INVENTION

In conventional transflective liquid crystal display devices, a single pixel has a

transmissive region and a reflective region, and each mode uses only light rays in a respective region. In other words, the reflective mode uses only light rays reflected in the reflective region, while the transmissive mode uses only light rays transmitted through the transmissive region.

5 In the reflective mode, since the outside light reflected in the reflective region is used, there is a demand to increase an amount of reflected light as possible. However, in the conventional transflective liquid crystal display devices, the light incident upon the transmissive region is not used and becomes wasted light in the reflective mode. For example, when the reflective region occupies 70% of a pixel, 30% of light, which passes  
10 though the transmissive region, is wasted. Therefore, it is not possible to obtain a sufficient amount of reflected light.

In the view of the foregoing, it is an object of the present invention to provide a transflective liquid crystal display device in which an amount of reflected light can be increased in a reflective mode and method of manufacturing the same.

15 A transflective liquid crystal display device of the present invention has a liquid crystal panel which has a transmissive region and a reflective region in each pixel and which is constructed of a first substrate and a second substrate faced with each other, and is characterized in that the first substrate has a reflecting member arranged in a first region other than the transmissive region in each pixel, and the second substrate has a scattering  
20 member arranged in at least part of the transmissive region.

According to this arrangement, since at least part of the transmissive region on the second substrate has a scattering member, the outside light passing through the transmissive region is scattered by the scattering member in the reflective mode. The scattered light enters the reflective region and the reflecting member reflects the entered light. Thus, in the  
25 reflective mode, it is possible to use the light reflected by the reflecting member in the reflective region and the light which is scattered by the scattering member in the transmissive region and then enters the reflective region. As a result, an amount of reflected light can be increased in the reflective mode.

In the transflective liquid crystal display device of the present invention, it is  
30 preferable that the second substrate has other scattering member arranged in a second region corresponding to the first region, and that the other scattering member has a lower scattering effect than that of the scattering member.

A transflective liquid crystal display device of the present invention has a liquid crystal panel which has a transmissive region and a reflective region in each pixel and which

is constructed of a first substrate and a second substrate faced with each other, and is characterized in that the first substrate has a reflecting member arranged in a first region other than the transmissive region in each pixel, and the second substrate has a first color filter having a scattering effect arranged in at least part of the transmissive region and a second color filter arranged in a second region corresponding to the first region.

According to this arrangement, since at least part of the transmissive region on the second substrate has a first color filter having a scattering effect, the outside light passing through the transmissive region is scattered by the first color filter in the reflective mode. The scattered light enters the reflective region and the reflecting member reflects the entered light. Thus, in the reflective mode, it is possible to use the light reflected by the reflecting member in the reflective region and the light which is scattered by the first color filter in the transmissive region and then enters the reflective region. As a result, an amount of reflected light can be increased in the reflective mode.

In the transflective liquid crystal display device of the present invention, it is preferable that the first color filter has a color different from that of the second color filter.

A method of manufacturing a transflective liquid crystal display device of the present invention is to manufacture a transflective liquid crystal display device having a liquid crystal panel which has a transmissive region and a reflective region in each pixel and which is constructed of a first substrate and a second substrate faced with each other, and has the steps of arranging a reflecting member in a first region other than the transmissive region of the first substrate, and arranging a scattering member in at least part of the transmissive region of the second substrate.

According to this method, it is possible to obtain a transflective liquid crystal display device capable of using in the reflective mode the light reflected by the reflecting member in the reflective region and the light which is scattered by the scattering member in the transmissive region and then enters the reflective region.

The method of manufacturing a transflective liquid crystal display device of the present invention further has the step of arranging other scattering member in a second region of the second substrate corresponding to the first region, where the other scattering member has a lower scattering effect than that of said scattering member.

A method of manufacturing a transflective liquid crystal display device having a liquid crystal panel of the present invention is to manufacture a transflective liquid crystal display device which has a transmissive region and a reflective region in each pixel and which is constructed of a first substrate and a second substrate faced with each other, and has

the steps of arranging a reflecting member in a first region other than the transmissive region of the first substrate, arranging a first color filter having a scattering effect in at least part of the transmissive region of the second substrate, and arranging a second color filter in a second region of the second substrate corresponding to the first region.

5           According to this method, it is possible to obtain a transflective liquid crystal display device capable of using in the reflective mode the light reflected by the reflecting member in the reflective region and the light which is scattered by the first color filter in the transmissive region and then enters the reflective region.

## 10   BRIEF DESCRIPTION OF THE DRAWINGS

Fig.1 is a sectional view showing a part of the pixel in a transflective liquid crystal display device according to Embodiment 1 of the present invention;

Fig.2 is a sectional view showing a part of the pixel in a transflective liquid crystal display device according to Embodiment 2 of the present invention;

15           Fig.3 is a sectional view showing a part of the pixel in a transflective liquid crystal display device according to Embodiment 3 of the present invention; and

Fig.4 is a view showing an arrangement of the pixel in a transflective liquid crystal display device of the present invention.

## 20   DESCRIPTION OF THE PREFERRED EMBODIMENT(S)

A subject matter of the present invention is in a transflective liquid crystal display device having a liquid crystal panel which has a transmissive region and a reflective region in each pixel in a pair of substrates faced with each other, forming a scattering member in at least part of the transmissive region on one of the substrates, thereby using in a reflective  
25   mode the light reflected by a reflecting member in the reflective region and the light which is scattered by the scattering member in the transmissive region and then enters the reflective region, and thus increasing an amount of reflected light in the reflective mode.

Embodiments of the present invention will be described specifically below with reference to accompanying drawings.

### 30   [Embodiment 1]

This embodiment explains a case of forming a scattering member in a transmissive region in a pixel, scattering outside light transmitted through the transmissive region so that part of the light goes to a reflective region, and thus increasing an amount of reflected light.

Fig.1 is a sectional view showing a part of the pixel in a transflective liquid crystal

display device according to Embodiment 1 of the present invention. In other words, Fig. 1 shows either one of an R region  $1_R$ , G region  $1_G$  and B region  $1_B$  in a pixel 1 shown in Fig. 4, and herein, is assumed to show the R region  $1_R$ . This embodiment explains an active-matrix liquid crystal display device. In addition, in Fig. 1, while optical elements are actually present such as a liquid crystal layer, electrodes, color filters and polarizers, descriptions on the elements are omitted to simplify the explanation.

Reference numeral 10 in Fig. 1 denotes a liquid crystal panel of the transfective liquid crystal display device. The liquid crystal panel 10 has a first glass substrate 101 that is a first substrate and a second glass substrate 105 that is a second substrate. A backlight 11 that is a light source in a transmissive mode is placed on the outside of the liquid crystal panel 10.

A transmissive region 102 and reflective region 103 are arranged in the R region. The transmissive region 102 has a rectangular shape and is arranged in the center portion of the R region. The reflective region 103 is arranged around the transmissive region 102.

A reflecting layer 104 that is a reflecting member is formed in the reflective region 103 of the first glass substrate 101. A metal thin film with optically reflecting function such as aluminum may be used as the reflecting layer 104.

A scattering layer 106 that is a scattering member is formed in the transmissive region 102 of the second glass substrate 105. A thin film with light scattering function may be used as the scattering layer 106. For example, a transparent thin film containing transparent resin particles (materials with a scattering effect) with a refractive index different from that of a matrix of the thin film may be used. In this case, the transparent resins and color resist may be used as the matrix. Materials of the matrix and transparent resin particle are not limited particularly, as long as the matrix is different in refractive index from the resin particle. For example, polycarbonate resin and acrylic resin may be used. In addition, the scattering layer 106 is only required to be formed in at least part of the transmissive region 102.

Predetermined wiring and active elements such as TFT are provided on the first glass substrate 101 having the arrangement, while a color filter and ITO electrode that is a common electrode are provided on the second glass substrate 105.

The function of the transfective liquid crystal display device with the above-mentioned arrangement will be described below. First, in the transmissive mode, light from the backlight 11 is passed through the transmissive region 102 and output to the outside. Specifically, as shown in Fig. 1, the light emitted from the backlight 11 is passed

through the first glass substrate 101, and only light rays (arrows g and h) passed through the transmissive region 102 are output to the outside through the scattering layer 106 and second glass substrate 105. Meanwhile, light rays from the backlight 11 in the reflective region 103 are reflected by the reflecting layer 104, and not output to the outside.

5 In the reflective mode, light (outside light) from the outside is reflected in the reflective region 103 and output to the outside. Specifically, as shown in Fig. 1, outside light rays (arrows a to d) are passed through the second glass substrate 105. Light rays (arrows a and b) in the reflective region 103 are reflected by the reflecting layer 104 on the first glass substrate 101, passed through the second glass substrate 105, and then output to the outside.  
10 Light rays (arrows c and d) in the transmissive region 102 are scattered by the scattering layer 106 on the second glass substrate 105, and part of the light rays enter the reflective region 103. Therefore, the part of light rays (arrows e and f) scattered by the scattering layer 106 are reflected by the reflecting layer 104 on the first glass substrate 101. In addition, light rays in the transmissive region 102 do not reach the reflecting layer 104, and therefore, are  
15 not used in the reflective mode.

In this way, in the reflective mode, since light rays in the transmissive region 102 are scattered by the scattering layer 106, enter the reflective region 103 and are reflected by the reflecting layer 104, the light rays scattered by the scattering layer 106 and then reflected by the reflecting layer 104 are added in predetermined rate to light rays reflected by the  
20 reflecting layer 104 in the reflective region 103. As a result, an amount of reflected light output to the outside is increased.

A method will be described below of manufacturing the transfective liquid crystal display device according to this embodiment. A case will be described below where the reflecting layer 104 is formed on the first glass substrate 101. First, a thin film composing  
25 the reflecting layer 104 is deposited on the first glass substrate 101. General CVD (Chemical Vapor Deposition) and sputtering may be used as a method of forming a thin film.

Next, a resist is coated on the thin film and baked, and thus a resist layer is formed on the thin film. Then, the resist layer is exposed to the light using a mask with an opening corresponding to the transmissive region 102 and developed, thereby removing the resist  
30 layer of the transmissive region 102 of the reflecting layer 104. Subsequently, the exposed reflecting layer 104 is etched and the resist layer remaining on the reflecting layer 104 is removed. In this way, the reflecting layer 104 with an opening for the transmissive region 102 is formed on the first glass substrate 101.

A case will be described next where the scattering layer 106 is formed on the second

glass substrate 105. First, a thin film composing the scattering layer 106 is deposited on the second glass substrate 105. For example, a transparent thin film composed of materials containing materials with a scattering effect (transparent resin particles with a refractive index different from that of a matrix of the thin film) may be used as the thin film. For example, general screen-printing may be used as a method of forming a thin film.

Next, a resist is coated on the transparent thin film and baked, and thus a resist layer is formed on the transparent thin film. Then, the resist layer is exposed to the light using a mask with an opening corresponding to the reflective region 103 and developed, thereby removing the resist layer of the reflective region 103 of the scattering layer 106.

Subsequently, the exposed scattering layer 106 is etched and the resist layer remaining on the scattering layer 106 is removed. In this way, the scattering layer 106 is formed in the transmissive region 102 on the second glass substrate 105.

Thus, according to this embodiment, it is possible to obtain a transreflective liquid crystal display device capable of using in the reflective mode the light reflected by the reflecting member in the reflective region and the light which is scattered by the scattering member in the transmissive region and then enters the reflective region.

#### [Embodiment 2]

This embodiment explains a case of forming a scattering member with a relatively high scattering effect in a transmissive region in a pixel, further forming a scattering member with a relatively low scattering effect in a reflective region, scattering outside light transmitted through the transmissive region so that part of the light goes to the reflective region, and thus increasing an amount of reflected light.

Fig.2 is a sectional view showing a part of the pixel in a transreflective liquid crystal display device according to Embodiment 2 of the present invention. In other words, Fig.2 shows either one of an R region  $1_R$ , G region  $1_G$  and B region  $1_B$  in a pixel 1 shown in FIG.4, and herein, is assumed to show the R region  $1_R$ . This embodiment explains an active-matrix liquid crystal display device. In addition, in Fig.2, while optical elements are actually present such as a liquid crystal layer, electrodes, color filters and polarizers, descriptions on the elements are omitted to simplify the explanation. Further, in Fig.2, the same portions as in Fig.1 are assigned the same reference numerals as in Fig.1 to omit specific descriptions thereof.

The first glass substrate 101 of the liquid crystal panel 20 shown in Fig.2 is the same as that in Embodiment 1. The transmissive region 102 on the second glass substrate 105 of the liquid crystal panel 20 is provided with a first scattering layer 201 that is a scattering



member with a relatively high scattering effect. The reflective region 103 on the second glass substrate 105 is provided with a second scattering layer 202 that is a scattering member with a relatively low scattering effect. A thin film with light scattering function may be used as the first and second scattering layers 201, 202. For example, a transparent thin film containing transparent resin particles with a refractive index different from that of a matrix of the thin film. Materials of the matrix and transparent resin particles are the same as those in Embodiment 1. The scattering effect can be adjusted by varying the content of the material (for example, transparent resin particle) with the scattering effect. For example, increasing the content of the material with the scattering effect increases the scattering effect, while decreasing the content of the material with the scattering effect decreases the scattering effect.

Predetermined wiring and active elements such as TFT are provided on the first glass substrate 101 having such an arrangement, while a color filter and ITO electrode that is a common electrode are provided on the second glass substrate 105.

The function of the transfective liquid crystal display device with the above-mentioned arrangement will be described below.

First, in the transmissive mode, light from the backlight 11 is passed through the transmissive region 102 and output to the outside. Specifically, as shown in Fig.2, the light emitted from the backlight 11 is passed through the first glass substrate 101, and only light rays (arrows g and h) passed through the transmissive region 102 are output to the outside through the first scattering layer 201 and second glass substrate 105. Meanwhile, light rays from the backlight 11 in the reflective region 103 are reflected by the reflecting layer 104, and not output to the outside.

In the reflective mode, light (outside light) from the outside is reflected in the reflective region 103 through the second scattering layer 202 on the second glass substrate 105 and output to the outside. Specifically, as shown in Fig.2, outside light rays (arrows a to d) are passed through the second glass substrate 105. Light rays (arrows a and b) in the reflective region 103 are reflected by the reflecting layer 104 on the first glass substrate 101 through the second scattering layer 202 on the second glass substrate 105, passed through the second scattering layer 202 and the second glass substrate 105, and then output to the outside. Light rays (arrows c and d) in the transmissive region 102 are scattered by the first scattering layer 201 on the second glass substrate 105, and part of the light rays enter the reflective region 103. Therefore, the part of light rays (arrows e and f) scattered by the first scattering layer 201 are reflected by the reflecting layer 104 on the first glass substrate 101. In

addition, light rays in the transmissive region 102 do not reach the reflecting layer 104, and therefore, are not used in the reflective mode.

In this way, in the reflective mode, since light rays in the transmissive region 102 are scattered by the first scattering layer 201, enter the reflective region 103 and are reflected by the reflecting layer 104, the light rays scattered by the first scattering layer 201 and then reflected by the reflecting layer 104 are added in predetermined rate to light rays reflected by the reflecting layer 104 in the reflective region 103. As a result, an amount of reflected light output to the outside is increased.

A method of manufacturing the transfective liquid crystal display device according to this embodiment will be described below.

The reflecting layer 104 is formed on the first glass substrate 101 in the same way as in Embodiment 1. Further, the processes up to forming the first scattering layer 201 in the transmissive region 102 of the second glass substrate 105 are the same as in Embodiment 1.

When the second scattering layer 202 is formed in the reflective region 103 on the second glass substrate 105, a thin film composing the second scattering layer 202 is coated on the second glass substrate 105. For example, a transparent thin film composed of materials (with a scattering effect lower than that of the first scattering layer 201) containing materials with the scattering effect (transparent resin particles with a refractive index different from that of a matrix of the thin film) may be used as the thin film. General screen printing may be used as a method of forming a thin film.

Next, a resist is coated on the transparent thin film and baked, and thus a resist layer is formed on the transparent thin film. Then, the resist layer is exposed to the light using a mask with an opening corresponding to the transmissive region 102 and developed, thereby removing the resist layer of the transmissive region 102 of the second scattering layer 202. Subsequently, the exposed transparent thin film is etched and the resist layer remaining on the second scattering layer 202 is removed. In this way, the second scattering layer 202 is formed in the reflective region 103 on the second glass substrate 105.

Thus, according to this embodiment, it is possible to obtain a transfective liquid crystal display device capable of using in the reflective mode the light reflected by the reflecting member in the reflective region and the light which is scattered by the first scattering member in the transmissive region and then enters the reflective region. Further, in this embodiment, since the reflective region also has the scattering function, it is possible to perform practical display without providing a scattering reflector, for example, due to out-of-cell scattering film or asperities.

**[Embodiment 3]**

This embodiment explains a case of forming a color filter with a scattering effect in a transmissive region in a pixel, further forming a color filter without scattering effect in a reflective region, scattering outside light transmitted through the transmissive region so that part of the light goes to the reflective region, and thus increasing an amount of reflected light.

Fig.3 is a sectional view showing a part of the pixel in a transfective liquid crystal display device according to Embodiment 3 of the present invention. In other words, Fig.3 shows either one of an R region  $1_R$ , G region  $1_G$  and B region  $1_B$  in a pixel 1 shown in FIG4, and herein, is assumed to show the R region  $1_R$ . This embodiment explains an active-matrix liquid crystal display device. In addition, in Fig.3, while optical elements are actually present such as a liquid crystal layer, electrodes, and polarizers, descriptions on the elements are omitted to simplify the explanation. Further, in Fig.3, the same portions as in Fig.1 are assigned the same reference numerals as in Fig.1 to omit specific descriptions thereof.

The first glass substrate 101 of the liquid crystal panel 20 shown in Fig.3 is the same as that in Embodiment 1. The transmissive region 102 on the second glass substrate 105 of the liquid crystal panel 20 is provided with a first color filter 301 with the scattering effect. The reflective region 103 on the second glass substrate 105 of the liquid crystal panel 20 is provided with a color filter 302 without the scattering effect. The first color filter 301 is composed of a colored resin containing materials with the scattering effect, for example, transparent resin particles with a refractive index different from that of a matrix, and thus exhibits the scattering effect. Materials for use in the matrix and transparent resin particles are the same as those in Embodiment 1.

Predetermined wiring and active elements such as TFT are provided on the first glass substrate 101 having such an arrangement, while an ITO electrode that is a common electrode is provided on the second glass substrate 105.

The function of the transfective liquid crystal display device with the above-mentioned construction will be described below. First, in the transmissive mode, light from the backlight 11 is passed through the transmissive region 102 and output to the outside. Specifically, as shown in Fig.3, the light emitted from the backlight 11 is passed through the first glass substrate 101, and only light rays (arrows g and h) passed through the transmissive 102 are output to the outside through the first color filter 301 and second glass substrate 105. Meanwhile, light rays from the backlight 11 in the reflective region 103 are reflected by the reflecting layer 104, and not output to the outside.

In the reflective mode, light (outside light) from the outside is reflected in the

reflective region 103 through the second color filter 302 on the second glass substrate 105 and output to the outside. Specifically, as shown in Fig.3, outside light rays (arrows a to d) passes through the second glass substrate 105. Light rays (arrows a and b) in the reflective region 103 are reflected by the reflecting layer 104 on the first glass substrate 101 through the second color filter 302 on the second glass substrate 105, passed through the second color filter 302 and the second glass substrate 105, and then output to the outside. Light rays (arrows c and d) in the transmissive region 102 are scattered by the first color filter 301 on the second glass substrate 105, and part of the light rays enter the reflective region 103. Therefore, the part of light rays (arrows e and f) scattered by the first color filter 301 are reflected by the reflecting layer 104 on the first glass substrate 101. In addition, light rays in the transmissive region 102 do not reach the reflecting layer 104, and therefore, are not used in the reflective mode.

In this way, in the reflective mode, since light rays in the transmissive region 102 are scattered by the first color filter 301, enter the reflective region 103 and are reflected by the reflecting layer 104, the light rays scattered by the first color filter 301 and then reflected by the reflecting layer 104 are added in predetermined rate to light rays reflected by the reflecting layer 104 in the reflective region 103. As a result, an amount of reflected light output to the outside is increased.

A method of manufacturing the transfective liquid crystal display device according to this embodiment will be described below. The reflecting layer 104 is provided on the first glass substrate 101 in the same way as in Embodiment 1.

A thin film of colored resin composing the first color filter 301 is deposited on the second glass substrate 105. The colored resin contains, as a material with the scattering effect, for example, transparent resin particles with a refractive index different from that of the colored resin. For example, general screen-printing may be used as a method of coating a thin film of colored resin. A resin colored with pigments or dyes and color resist may be used as the colored resin.

Next, a resist is coated on the thin film of colored resin and baked, and thus a resist layer is formed on the thin film of colored resin. Then, the resist layer is exposed to the light using a mask with an opening corresponding to the reflective region 103 and developed, thereby removing the resist layer of the reflective region 103 on the first color filter 301. Subsequently, the exposed thin film is etched and the resist layer remaining on the first color filter 301 is removed. In this way, the first color filter 301 is formed on the transmissive region 102 on the second glass substrate 105.

Then, a thin film of colored resin composing the second color filter 302 is deposited on the second glass substrate 105. For example, general screen-printing may be used as a method of coating a thin film of colored resin.

Specifically, a resist is coated on the thin film of colored resin and baked, and thus a  
5 resist layer is formed on the thin film of colored resin. Then, the resist layer is exposed to the light using a mask with an opening corresponding to the transmissive region 102 and developed, thereby removing the resist layer of the transmissive region 102 of the second color filter 302. Subsequently, the exposed thin film is etched and the resist layer remaining  
10 on the second color filter 302 is removed. In this way, the second color filter 302 is formed on the reflective region 103 on the second glass substrate 105. The first and second color filters are formed in the G region and B region in the same way as described above.

Thus, according to this embodiment, it is possible to obtain a transfective liquid crystal display device capable of using in the reflective mode the light reflected by the reflecting member in the reflective region and the light which is scattered by the first color  
15 filter in the transmissive region and then enters the reflective region. In this case, since the first color filter 301 serves as the scattering member, the processes can be simplified as compared to Embodiments 1 and 2. In the case where the transmissive and reflective regions are provided with different colors or with different color concentrations, this embodiment does not increase processes, and thus, provides the efficiency in manufacturing.

20 In addition, this embodiment explains the case of using a method of patterning by photolithography using colored resin, as a method of forming a color filter. However, in the present invention, performing electrodeposition or printing on predetermined portions may form a color filter. In other words, it may be possible to directly form the first color filter 301 and the second color filter 302 respectively in the transmissive region 102 and reflective  
25 region 103 using the electrodeposition or printing. Further, while this embodiment explains the case where the second color filter is formed after the first color filter is formed, in the present invention the first color filter may be formed after the second color filter is formed.

The present invention is not limited to the above-mentioned embodiments, and is capable of being carried into practice with various modifications thereof. For example,  
30 while Embodiments 1 to 3 explain the case where the liquid crystal display device is an active-matrix type, the present invention is applicable to a case of a passive type of liquid crystal display device where the first and second substrates are provided with row electrodes or column electrodes.

Further in the present invention, the size and material of each structural element are

capable of being varied as appropriate without departing from the scope of the present invention. The above-mentioned Embodiments 1 to 3 describe CVD and sputtering as a method of forming a thin film composing the reflecting layer, and further describe screen printing as a method of forming a scattering layer, but the present invention is not limited to such methods. While the above-mentioned Embodiments 1 to 3 describes the case of using transparent resin particles as a material to provide the scattering effect, such a material is not limited to transparent resin particle as long as the material is capable of providing the scattering effect. The content of the material to provide the scattering effect is not limited particularly as long as the content is in a range for exhibiting the scattering effect.

As described above, according to a transfective liquid crystal display device according to the present invention, a liquid crystal panel is provided which has a transmissive region and a reflective region in each pixel and which has a first substrate and a second substrate faced with each other, and the first substrate has a reflecting member arranged in a region other than the transmissive region in each pixel, while the second substrate has a scattering member arranged in at least part of the transmissive region, whereby in the reflective mode, it is possible to use the light reflected by the reflecting member in the reflective region and the light scattered by the scattering member in the transmissive region and enters the reflective region.

**CLAIMS:**

1. A transflective liquid crystal display device comprising a liquid crystal panel, which  
5 has a transmissive region and a reflective region in each pixel, constructed of a first and a second substrate faced with each other, characterized in that said first substrate comprises a reflecting member arranged in a first region other than the transmissive region, and said second substrate comprises a scattering member arranged in at least part of the transmissive region.
- 10 2. A device according to claim 1, wherein said second substrate comprises other scattering member arranged in a second region corresponding to said first region, the other scattering member having a lower scattering effect than that of said scattering member.
3. A transflective liquid crystal display device comprising a liquid crystal panel, which  
15 has a transmissive region and a reflective region in each pixel, constructed of a first and a second substrate faced with each other, characterized in that said first substrate comprises a reflecting member arranged in a first region other than the transmissive region, and said second substrate comprises a first color filter having a scattering effect arranged in at least part of the transmissive region and a second color filter arranged in a second region corresponding to said first region.
- 20 4. A device according to claim 3, wherein said first color filter has a color different from that of said second color filter.
5. A method of transflective liquid crystal display device comprising a liquid crystal panel, which has a transmissive region and a reflective region in each pixel, constructed of a first and a second substrate faced with each other, comprising the steps of:  
25 arranging a reflecting member in a first region other than the transmissive region of said first substrate; and  
arranging a scattering member in at least part of the transmissive region of said second substrate.
6. A method according to claim 5, further comprising the step of arranging other  
30 scattering member in a second region of said second substrate corresponding to said first region, the other scattering member having a lower scattering effect than that of said scattering member.
7. A method of transflective liquid crystal display device comprising a liquid crystal panel, which has a transmissive region and a reflective region in each pixel, constructed of a

first and a second substrate faced with each other, comprising the steps of:

arranging a reflecting member in a first region other than the transmissive region of said first substrate;

5 arranging a first color filter having a scattering effect in at least part of the transmissive region of said second substrate; and

arranging a second color filter in a second region of said second substrate corresponding to said first region.






FIG. 1




FIG. 2




FIG. 3




FIG. 4

## INTERNATIONAL SEARCH REPORT

International Application No

PCT/IB 03/01462

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 7 G02F1/1335

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**Minimum documentation searched (classification system followed by classification symbols)  
IPC 7 G02F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2001/008437 A1 (KUBO MASUMI ET AL) 19 July 2001 (2001-07-19) paragraph '0059! - paragraph '0061!; figures 1A,1B	1,5
Y A	---	3,4,7 2,6
X	US 6 215 538 B1 (FUJIOKA SHOGO ET AL) 10 April 2001 (2001-04-10) figure 20; example 15	1,5
Y A	---	3,4,7 2,6
	--- -/--	

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

## \* Special categories of cited documents:

\*A\* document defining the general state of the art which is not considered to be of particular relevance

\*E\* earlier document but published on or after the international filing date

\*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

\*O\* document referring to an oral disclosure, use, exhibition or other means

\*P\* document published prior to the international filing date but later than the priority date claimed

\*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

\*Z\* document member of the same patent family

Date of the actual completion of the international search

4 August 2003

Date of mailing of the international search report

12/08/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Lord, R

## INTERNATIONAL SEARCH REPORT

International Application No.

PCT/IB 03/01462

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	AKINS R ET AL: "COLOR FILTERS WITH SCATTERING CENTERS FOR USE IN REFLECTIVE COLOR DIAPAYS" MOTOROLA TECHNICAL DEVELOPMENTS, MOTOROLA INC. SCHAUMBURG, ILLINOIS, US, vol. 41, May 2000 (2000-05), pages 15-16, XP001096638 ISSN: 0887-5286 the whole document	3,4,7
A	EP 1 113 308 A (MATSUSHITA ELECTRIC IND CO LTD) 4 July 2001 (2001-07-04) paragraph '0008! - paragraph '0009!; figure 3	1,3,5,7
A	US 2002/018159 A1 (KIM WOO HYUN ET AL) 14 February 2002 (2002-02-14) paragraph '0035! - paragraph '0038!; figures 2A,2B	1,3,5,7

## INTERNATIONAL SEARCH REPORT

International Application No

PCT/IB 03/01462

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2001008437 A1	19-07-2001	JP 2001272674 A	05-10-2001
US 6215538 B1	10-04-2001	JP 2000029012 A	28-01-2000
		JP 3335130 B2	15-10-2002
		JP 2000111902 A	21-04-2000
EP 1113308 A	04-07-2001	EP 1113308 A1	04-07-2001
		CN 1319195 T	24-10-2001
		WO 0104695 A1	18-01-2001
		JP 2001075091 A	23-03-2001
US 2002018159 A1	14-02-2002	KR 2002003758 A	15-01-2002